



E32-T11N 2M

Barrage, M4, angle droit, rayon de courbure 1 mm, E3X-DA-SE-S: 530 mm

Spécifications

Sensing method	Through-beam
Shape	Threaded
Size	M4
Application	Object detection
Features	90° cable exit, Flexible fiber, Hexagonal back
Temperature range	-40-70 °C
Sensing distance	3000 mm
Cable length	2 m
Bending radius	1 mm
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP67
Sensing surface orientation	Right-angle
Material sheath	PVC

Accessoires



E39-F1

Long-distance lens unit for E32 through-beam fibers with M2.6 thread

E39-F16

Long-distance lens unit for E32 through-beam fibers

Produits liés



E3NX-CA

Détection de repères colorés haute performance



E3NX-CA

Détection de repères colorés haute performance



E3NX-FA

Amplificateur à fibre numérique hautes performances



E3NX-MA

Amplificateurs à fibre intelligents



E3X-NA

Amplificateur à fibre numérique avec réglage par potentiomètre



E3X-ZV et E3X-MZV

Amplificateur à fibre intelligent

Téléchargements

Bibliothèque CAO



EAC Mark removal Avis d'interruption

EN PDF 221 ko



Fiber Sensor Selection Guide de sélection

EN PDF 16,2 Mo

CONDITIONS D'UTILISATION

Ce document PDF a été créé à partir du site Web européen d'OMRON Industrial Automation le 22 October, 2024. Cliquez ici pour consulter les [conditions d'utilisation](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU