


# 888 Roller with flange

**Use:** roller for trolleys or sliding doors. The flange allows us to use the profile grooves as track.

**Material** polyamide roller, galvanised steel nuts and bolts.

**State of supply** complete with 2 rigid radial ball bearings with 2 waterproof screens series 608, 1 M8x43 screw, 1 washer, 1 square nut.



**Loads recommended For Part 888 and 918**

Speed	rpm	0	6	13	19	25	32	64	127	191	255	318
	m/min	0	1	2	3	4	5	10	20	30	40	50
Load	N	260	176.5	88.2	63.5	49.4	35.3	17.6	8.8	6.3	4.9	3.5

Order code	Pack	Colour	Finishing screws	Weight g	Stock	€ piece
60946	12 pcs	black RAL9005	galvanised	91	✓	


# 918 Roller without flange

**Use:** to construct low-friction sliding surfaces.

**Material** polyamide roller, galvanised steel nuts and bolts.

**State of supply** complete with 2 rigid radial ball bearings with 2 waterproof screens series 608, 1 M8x43 screw, 1 washer, 1 square nut.

Part. 918



Part. 888

Order code	Pack	Colour	Finishing screws	Weight g	Stock	€ piece
65516	12 pcs	black RAL9005	galvanised	80	✓	